### ClearWater Tech, LLC

# **DEGASSING VALVE**

### For Continuous Automatic Venting

The automatic degassing valve manufactured by Plast-O-Matic Valves, Inc., allows for continuous venting of undissolved gas from the contacting vessel of an ozone treatment system. Placed at the high point of a piping system, this innovative valve will vent gas as it occurs. A unique float/actuating lever allows the vent orifice to open when gas is present. After gas vents, liquid forces the vent to close. Whenever gas accumulates, the valve will re-open until the gas is vented.



## **Specifications**

Body material available: Acrylic
Elastomers: FKM (Viton)

Additional wetted material: Natural polypropylene

Max. operating pressure: 100 psi
Min. specific gravity: 0.9

**Dimensions:** 4 1/4" high x 2 1/4" diameter

Vent port: 1/8 in. NFPT

**System connection:** 1/2 in. NFPT; valve must be orientated

vertical as illustrated above

# Flow Rate 1.6 1.4 1.2 1 0.8 0.6 0.4 0.2 0 10 20 30 40 50 60 70 80 90 100 Inlet (PSI)

### **Benefits**

- · Safety: Allows safe expulsion of unwanted air in piping systems
- Dependability: Patent-pending float mechanism assures minimal emission of system liquid prior to sealing
- Water Pressure: Higher pressure yields increased ozone solubility
- Cost Efficient: Designed to improve system performance and competitively priced
- Superior Design: Valve opens and closes automatically, over and over and over
- Corrosion Resistant: Top quality thermoplastics and elastomers resist chemical attack and protect system purity
- Reduces replacement costs: no internal or external metal components; ideal for aggressive environments
- Relief of undissolved ozone gas from the hydraulic line, to be vented to an ozone destruct system
- · Reduces potential off gassing of ozone downstream of the ozone system

### **Features**

- · Continuous automatic venting
- · Small compact construction
- Serviceable
- · See through acrylic material
- Viton elastomers

