

CONTACT VESSELS

Unit	"Use With" or (Packaged With)	Misc. Specifications	Min-Max GPM	Inlet/Outlet Dimension (inches)	Max Pressure	Dimensions (inches) (4) (ø = Diameter)			Wt. (lbs.) (4)
						H	W	D	lbs
CNT30 (30gal Tank)	(POE10)	Bottom Inlet/Outlet	40GPM Max	1.25 mpt / 1.25 mpt	75 PSI	44.000	16.000	ø	30.00
CNT40 (40gal Tank)	(POE15)	Bottom Inlet/Outlet	40GPM Max	1.25 mpt / 1.25 mpt	75 PSI	56.000	16.000	ø	38.00
CNT80 (80gal Tank)		Bottom Inlet/Outlet	40GPM Max	1.25 mpt / 1.25 mpt	75 PSI	67.000	21.000	ø	48.00
CNT120 (120gal Tank)		Bottom Inlet/Outlet	40GPM Max	1.25 mpt / 1.25 mpt	75 PSI	73.000	24.000	ø	68.00
CNT264 (264gal Tank)		Top Inlet/Bottom Outlet	180GPM Max	3.00 slp / 3.00 slp	150 PSI	100.000	36.500	ø	285.00
CNT463 (463gal Tank)		Top Inlet/Bottom Outlet	180GPM Max	3.00 slp / 3.00 slp	150 PSI	107.000	49.000	ø	900.00
CNT850 (850gal Tank)		Top Inlet/Bottom Outlet	300GPM Max	4.00 slp / 4.00 slp	150 PSI	122.000	64.000	ø	906.00
CNC15 (10gal Column)		Bottom Inlet/Outlet	80GPM Max	2.00 slp / 2.00 slp	75 PSI	76.000	23.000	11.250	75.00

NOTES:

4-This is the unit size and weight only and is not the shipping size and weight. Dimensions are given in inches and decimals, weight in pounds