

## OZONE CATALYTIC DESTRUCT SYSTEM

Unit	"Use With" or (Packaged With)	Misc. Specifications	Inlet/Outlet Dimension (inches)	Max Pressure	Duty Cycle	120V/60Hz, AMPS (1)	Intern. 220V/50Hz, AMPS, Single Hot Leg (1)	240V/60Hz, AMPS (1)	Dimensions (inches) (4)			Wt. (lbs) (4)
									H	W	D	
OCD	[Water Trap]	Destroys Ozone Off-gas From Contact Vessel	0.375 comp		Continuous	1.0	0.6	0.5	21.000	11.500	4.250	12.00
Water Trap	[OCD - Ozone Catalytic Destruct]	Separates Water And Gas Prior To Ozone Destruct	0.250 comp/ 0.375 comp						33.000	9.000	3.000	7.00
VAS7	CNT264, CNT463, CNT850	Contact Tank Off Gas Vent	0.75 fpt / 0.50 fpt	150 PSI					7.000	3.500		1.00
VAS8	CNT30, CNT40, CNT80, CNT120	Contact Tank Off Gas Vent	0.75 mpt / 0.25 comp	150 PSI					8.000	4.000		1.00

**NOTES:**

1-The Amp rating in this section is for the product only and does not include any peripheral equipment, unless the equipment is considered built into the product  
4-This is the unit size and weight only and is not the shipping size and weight. Dimensions are given in inches and decimals, weight in pounds